

Homogenizer HST - HLE18.5

Standart Capacity 2.500 LT/H
 Standard homogenization pressure 200 Bar
 Absorbed motor power: 18.5 kW
 Aseptic execution is optional
 Suitable for processing high viscosity products
 Unique design in accordance with the conditions of use
 simple installation, Ergonomic Design, Easy Maintenance

Weight with Motor: Approx 1100 kg
 Technical changes reserved!



Model	Max. Capacity	Max. Pressure
HST-HLE18.5	LT/H (Capacity)	Bar (Working Pressure)
HLE18.5-120	4000	120
HLE18.5-170	3000	170
HLE18.5-200	2500	200
HLE18.5-250	2000	250
HLE18.5-300	1600	300
HLE18.5-400	1250	400
HLE18.5-500	850	500
HLE18.5-600	650	600
HLE18.5-750	400	750
HLE18.5-1000	350	1000

Model	Max. Speed	Max. Diameter
HST-HLE18.5	RPM (Speed)	MM (Diameter)
HLE18.5-120	160	55
HLE18.5-170	160	50
HLE18.5-200	165	45
HLE18.5-250	140	45
HLE18.5-300	122	40
HLE18.5-400	122	35
HLE18.5-500	120	30
HLE18.5-600	120	25
HLE18.5-750	120	20
HLE18.5-1000	120	16

