

Homogenizer HST- HLE55

- Standart Capacity 7.500 LT/H
- Standard homogenization pressure 200 Bar
- Absorbed motor power: 55 kW
- Aseptic execution is optional
- Suitable for processing high viscosity products
- Unique design in accordance with the conditions of use
- simple installation, Ergonomic Design, Easy Maintenance

Weight with Motor: Approx 2800 kg
 Technical changes reserved!



Model	Max. Capacity	Max. Pressure
HST-HLE55	LT/H (Capacity)	Bar (Working Pressure)
HLE55-150	10000	150
HLE55-200	7500	200
HLE55-250	5500	250
HLE55-300	4500	300
HLE55-350	4000	350
HLE55-400	3000	400
HLE55-500	2500	500
HLE55-600	2000	600
HLE55-750	1500	750
HLE55-850	1000	850
HLE55-1000	750	1000

Model	Max. Speed	Max. Diameter
HST-HLE55	RPM (Speed)	MM (Diameter)
HLE55-150	135	90
HLE55-200	135	80
HLE55-250	128	70
HLE55-300	135	60
HLE55-350	122	60
HLE55-400	105	40
HLE55-500	108	45
HLE55-600	114	40
HLE55-750	114	35
HLE55-850	101	30
HLE55-1000	107	25

