

# Homogenizer HST- HLE75

- Standart Capacity 10.000 LT/H
- Standard homogenization pressure 200 Bar
- Absorbed motor power: 75 kW
- Aseptic execution is optional
- Suitable for processing high viscosity products
- Unique design in accordance with the conditions of use
- simple installation, Ergonomic Design, Easy Maintenance

Weight with Motor: Approx 2800 kg  
 Technical changes reserved!



Model	Max. Capacity	Max. Pressure
HST-HLE75	LT/H (Capacity)	Bar (Working Pressure)
HLE75-150	12500	150
HLE75-200	10000	200
HLE75-250	8000	250
HLE75-300	6000	300
HLE75-350	5000	350
HLE75-400	4000	400
HLE75-500	3000	500
HLE75-600	2500	600
HLE75-750	2000	750
HLE75-850	1500	850
HLE75-1000	1000	1000

Model	Max. Speed	Max. Diameter
HST-HLE75	RPM (Speed)	MM (Diameter)
HLE75-150	135	90
HLE75-200	135	80
HLE75-250	128	70
HLE75-300	135	60
HLE75-350	122	60
HLE75-400	105	40
HLE75-500	108	45
HLE75-600	114	40
HLE75-750	114	35
HLE75-850	101	30
HLE75-1000	107	25

